Todaybulb



Product Description

U shaped CFL

U shaped CFL lamp is a type of energy saving lighting solution designed to replace incandescent bulb. Common models of CFL U type bulb include 2U CFL lamp, 3U CFL lamp and 4U CFL lamp. The special twisted "U" shape tube and standard E27 lamp base make it a widely used in homes and businesses.

Advantage

- Save energy

U shaped CFL lamp uses up to 70% less energy than traditional incandescent bulbs that can save money on your electricity bill.

- Long lifespan

U shaped CFL is very durable with 8000 hours life span, reducing the maintenance cost and replacement cost.

- Cost-Effective

U shaped CFL lamp is more energy efficiency than incandescent bulb and cheaper than LED bulb. It is a very cost-effective lighting solution for those on a budget.

- Compact U design

With U shape appearance make U shaped CFL lamp emitting more evenly and broadly light. And due to the short size, it is suitable to fit in small lighting fixtures.



Compact U shape



Standard E27 or B22 base

PBT material

Todaybulb

U shaped CFL

Feature

- ✓ Compact U shape
- ✓ Cost-effective
- ✓ Halogen powder with 3000 hours life span, CRI>70
- ✓ Tri-phosphor powder with 8000 hours life span, CRI>80

Application

- Indoor lighting

-Chandeliers: Providing soft and diffused light, U shaped CFL light is widely used in chandeliers shades for kitchen and living room.
-Table lights and floor light: Designed with small size, U shaped CFL light is fitted in table and floor lights to create a comfortable lighting environment for reading and working.

- Outdoor lighting

- Porch light: The features of long life span, energy saving and easy to install make U shaped CFL light widely used in porch light.





Specification

Halogen Powder

Model	Appearance	Base	Wattage	Dimension (mm)			Luminous Flux	Color Temperature	CRI (Ra)	Voltage
				L	D1	D2				
CFL-U	2U	E27 Base Or B22 Base	5W	115	40	9	175LM	3000K-6500K	≥70 (Halogen powder)	220-240V 110-130V
CFL-U			9W	135	40	9	315LM			
CFL-U			11W	135	40	9	385LM			
CFL-U			15W	155	40	9	525LM			
CFL-U			20W	155	40	9	700LM			
CFL-U	3U		26W	170	50	12	910LM			
CFL-U			30W	170	50	12	1050LM			
CFL-U			36W	170	50	12	1260LM			
CFL-U			40W	170	50	12	1400LM			
CFL-U	4U		45W	260	70	16	1575LM			
CFL-U			65W	260	70	16	2275LM			

Todaybulb

U shaped CFL

Tri-phosphor Powder

Model	Appearance	Base	Wattage	Dimension (mm)			Luminous Flux	Color Temperature	CRI (Ra)	Voltage
				L	D1	D2				
CFL-U	2U	E27 Base Or B22 Base	5W	115	40	9	300LM	3000K-6500K	≥80 (Tri-phosphor powder)	220-240V 110-130V
CFL-U			9W	135	40	9	540LM			
CFL-U			11W	135	40	9	660LM			
CFL-U			15W	155	40	9	900LM			
CFL-U			20W	155	40	9	1200LM			
CFL-U	3U		26W	170	50	12	1560LM			
CFL-U			30W	170	50	12	1800LM			
CFL-U			36W	170	50	12	2160LM			
CFL-U			40W	170	50	12	2400LM			
CFL-U	4U		45W	260	70	16	2700LM			
CFL-U			65W	260	70	16	3900LM			

Dimensional Drawing

